## ExtlO-Module

The HiRes Video Company **MOBOTIX** 



## **ExtlO Opens New Horizons For Cameras**

With its new ExtIO module, MOBOTIX leads the way to completely new technology. The ExtIO can be connected to a camera either directly via USB or through a network and extends the MOBOTIX camera to a high-performance audio unit with microphone and speaker, infrared motion detector, temperature sensor and additional switch in-/outputs. Door and gate intercom systems are easy to implement using the two illuminated buttons.

Technical Specifications ExtlO				
Interfaces	USB, Ethernet 10/100 Mbps	Status display	2 status LEDs	
Audio	Microphone and speaker, integrated amplifier and equalizer, Line-In/Line-Out	Certificates	EMC (EN55022, EN55024, EN61000-6-2, FCC part15B, AS/NZS3548)	
Input contacts	2 signal inputs (galvanically separated) Safety extra-low voltage, SELV (AC/DC) Switching voltage of ExtlO provided (also external)	Operating conditions	IP65 (DIN EN 60529)	
		Operating temperature	-30 to +60 °C (-22 to +140 °F) (DIN EN 50125)	
		Power supply	USB, Power over Ethernet (IEEE 802.3af; Class 2)	
Output contacts	2 signal outputs (potential-free) Safety extra-low voltage, SELV (AC/DC), up to 100 mA	Power input	typ. 1 W	
		Dimensions	Ø x H: 16 x 4,5 cm, compatible with D24 accessories	
Sensors	Passive IR motion detector (PIR) Temperature sensor for environmental temperature Illumination sensor 2 illuminated buttons	Weight	ca. 430 g	
		Standard delivery	Housing (high-resistance composites – PBT), white, speaker cable, mounting parts, patch cable, manual	



## **HiRes Video Innovations**

The German company MOBOTIX AG is known as the leading pioneer in network camera technology and its decentralized concept has made high-resolution video systems cost efficient.